PET Film Double Side Adhesive Tape

BOW NO. 3503BM

Technical Data 2021

BOW TAPE

Description

Acrylic adhesive is double coated on Black PET Film carrier.
The film carrier allows for ease of conversion and die cutting.


Application

- LCD BLU Top chassis panel sheet
- Light weight stainless steel and aluminum panel bonding

Properties


Color	Black
Thickness	0.03mm (± 10㎛)
Carrier	PET Film
Liner	PET Film + PET Film
Standard Size	1000mm x 50M, 100M

Structure



Performance

180˚ Peel Adhesion		
	SUS	1300
	PC	1200
	GLASS	1200
Dynamic Shear		7
Heat/Temperature Resistance		
Short Term		150°C
Long Term		80°C
UV Resistance		++
Chemical Resistance		++

	180˚ Adhesion ASTM D3330	Dynamic Shear ASTM D1002
		
Substrate	As Indicated	SUS
Speed/Load	300mm/min	200mm/min
Tape size	25mm	1.00㎠
Spec in	-	-
Unit	gf/25mm	kgf/㎠

Shelf Life

24 months from date of manufacture when stored at 21°C to 38°C (69°F to 100°F) and 50% relative humidity.

Caution

Technical Specifications reflect the average performance of products based on data from controlled standard testing enviroments and engineering experience but are not guaranteed. Although Bow Tape products are suitable for most standard situations, due to many unforeseeable factors contributing to the performance during the application process, Bow Tape should be consulted with proper information for accurate product suggestions regarding specific usage.

Bow Tape Co.,ltd
701-5, Baran-ro, Hyangnam-eup Hwaseong-si, Gyeonggi-do, Korea 18625
+82-31-353-6780 bowtape@bowtape.com
www.bowtape.com